

SD Series

Rotary Valve for Metering
and Airlock Applications



SECTOR INDUSTRIES:



Plastics



Pet Food



Construction



Food



Pharmaceutical
and Cosmetics



Chemical

FEATURES

- | | |
|--|---|
| <ul style="list-style-type: none"> Available in 4 heights, from 10"H to 18 1/4"H; and 4 square-flange sizes from 6" to 12". | <ul style="list-style-type: none"> Excellent performance in high-temperature applications up to 250°F. |
| <ul style="list-style-type: none"> This ACS Valves Pre-fit Performance™ Series valve enables simple and fast drop-in replacement of Meyer® type SD rotary valves. | <ul style="list-style-type: none"> Cast iron housing. |
| <ul style="list-style-type: none"> Valve housing cast in North America; ensures superior strength and solidification of housing's metallurgy. | <ul style="list-style-type: none"> 6-vane or 8-vane rotor with beveled tips and sides. |
| <ul style="list-style-type: none"> CNC-machined components and housing provide precision tolerances; eliminates axial shaft movement, extends maintenance cycles. | <ul style="list-style-type: none"> Direct-drive motor package. |

SPECIFICATIONS:

INLET/OUTLET
FLANGE SIZES:

4 sizes from 6" to 12"

MATERIAL OF
CONSTRUCTION:

Cast Iron,
Stainless Steel

PRESSURE
DIFFERENTIAL:

-

HIGH TEMPERATURE
RANGE:

250°F