

Product Specifications

AN-X Series Valve

Dust Collector Valve for airlock applications

The AN-X Valve is an NFPA compliant dust collector valve for any application. Complete with steel rotor tips and outboard bearings, this valve is great for easy, drop-in replacements for FT or AN dust collection valves.

SECTOR INDUSTRIES:















FEATURES

- · Mild Steel construction
- Rotor with steel rotor tips
- Heavy-duty construction
- Direct-drive operation
- Tight internal clearances
- ACST-4[™] glandless Teflon® shaft seal

BENEFITS

NFPA compliant
 Outboard bearings
 Steel tips
 Easy drop-in replacements

VALVE ROTARY VALVE CAPACITY (CUBIC FEET/HOUR)

8"	0.64
10"	1.34
12"	2.46

Capacities shown are based on 100% pocket-fill efficiency. Pocket-fill efficiencies vary by application. To ensure optimal efficiency, contact ACS Valves.

SPECIFICATIONS:	INLET/OUTLET FLANGE SIZES:	MATERIAL OF CONSTRUCTION:	PRESSURE DIFFERENTIAL:	HIGH TEMPERATURE RANGE:
	3 sizes from 8", 10", 12"	MIId Steel, Stainless Steel	Up to 15" psi	500°F