acsvalves.com • 905-765-2004 • 611 Argyle Street, North • Caledonia, Ontario N3W 1M1 • Canada ©Copyright 2023 ACS Valves

MATERIAL OF

CONSTRUCTION:

Cast Iron, XTR-Coat

HIGH TEMPERATURE

RANGE:

500°F

a chemically-resistant coating.

FEATURES

SECTOR INDUSTRIES:

• Resists wear and corrosion from chemicals, acid and abrasive material.

• Cast iron housing and endplates coated with XTR-Coat,

Plastics

Pet Food

- XTR-Coat also prevents material sticking and buildup on valve surfaces.
- USDA and FDA compliant.
- Rated for great performance in operating temperatures up to 500°F.

INLET/OUTLET

FLANGE SIZES:

Round flange 4" to 16"

- Handles pressure differentials up to 15 PSIG.
- Available sizes: Round flange 4" through 16".

SPECIFICATIONS:

ACS now offers XTR-Coat synergistic coatings to maximize performance in a variety of applications. XTR-Coat finishes provide wear and corrosion protection, reduced friction and non-stick performance. XTR-Coat finishes are a high-performance, non-toxic and FDA-compliant alternative to industrial chrome plating.

- · Expedites cleaning and sanitation operations; works well in washdown duty environments.
- Non-stick, food-grade properties for sugar, flour, pet food and other food processing applications.
- Dry-lubricity.
- Non-porous, moisture-proof surfaces and mold release.

PRESSURE

DIFFERENTIAL:

Up to 15 PSIG

Corrosion-resistant Rotary Valve

for Abrasive or Acidic Materials The XTR-MD Series valve boasts high corrosion resistance with the same efficient,

high-performance design of our popular round-flange MD Series rotary valve. Its unique properties are ideal for any pressure pneumatic conveying system that requires

food-grade product contact.

Need it in square flange? Check out our XTR-CI.







Product Specifications

Series

XTR-MD

